



# Tork Universal Asciugamani piegato a Z Flushable



## vantaggio

- Un asciugamano alla volta: riduzione dei consumi
- Elevata spappolabilità: nessun rischio di intasamento
- Ideale per i mezzi di trasporto (navi, aerei e treni)



Food contact approved certified by a third party

## caratteristiche del prodotto

articolo	sistema	Lunghezza aperto	Larghezza aperto	Lunghezza piegato	Larghezza piegato	Veli	Stampa	Embossing	Colore
290170	H3 - Sistema per asciugamani piegati a C e a Z	23 cm	23 cm	11.5 cm	23 cm	2	no	sì	Bianco

## dati spedizione

### unità consumer

EAN	7322540373479
pezzi	214
materiale	Banderole
altezza	130 mm
larghezza	230 mm
lunghezza	115 mm
volume	3.4 dm3
peso netto	498 g
peso lordo	505 g

### pallet

EAN	7322540373486
pezzi	89880
unità consumer	420
altezza	1844 mm
larghezza	800 mm
lunghezza	1200 mm
volume	1.6 dm3
peso netto	209.16 kg
peso lordo	229.24 kg

### unità di trasporto

EAN	7322540373509
pezzi	3210
unità consumer	15
materiale	Carton
altezza	242 mm
larghezza	406 mm
lunghezza	596 mm
volume	58.6 dm3
peso netto	7.47 kg
peso lordo	8.19 kg



## ambiente

### Content

Virgin pulp, fibres, Chemicals

### Material

Virgin fibre Virgin pulp fibres are produced out of softwood or hardwood. The process is either sulphite or sulphate delignification, meaning that e.g. lignins and resins are removed from cellulosic material. Bleaching of fibres Bleaching is a cleaning process of the fibres and the aim is to achieve a bright pulp, but also to get a certain purity of the fibre in order to achieve the demands for hygiene products and in some cases to meet the requirements for food safety.

There are different methods used today for bleaching ECF (elementary chlorine free) (where chlorine dioxide is used), and TCF (totally chlorine free) where ozone, oxygen and hydrogen peroxide is used.

### Chemicals

The chemicals used in the process as well as the functional chemicals are assessed from an environmental, occupational health and safety and product safety point of view. The used functional chemicals are: Dry strength agent Dye Fixing agents Fluorescent whitening agent Glue Softeners The process chemicals are: Antipitch Protection agent Yankee coating Defoamer Dispersing agents and surfactants pH and charge control Retention aids Broke treatment chemicals Drainage aid

### Packaging

Fulfilment of Packaging and Packaging Waste Directive (94/62/EC): Yes Environmental label = Ecolabel This product does not have any ecolabel

Date of issue 2007-04-10

Revision date 2010-03-12

### Production

Material produced at Mannheim mill and product converted at Kostheim mill, Germany, certified according to ISO 9001:2000, ISO 14001 and EMAS

### Destruction

This product is suitable to be taken care of in the normal sewage system of the community.